



SAFETY DATA SHEET

Simoniz 5 Wheel Silver

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY:

PRODUCT NAME: Simoniz 5 Wheel Silver
PART No.: SIMW50
IN-HOUSE No.: A786
EMERGENCY TELEPHONES: Out of office hours: +44 (0)786 675 5247
MANUFACTURER: Holt Lloyd
Oakhurst Drive
Cheadle
Manchester
Tel: +44 (0)161 491 7391
Fax: +44 (0)161 491 7399

2. COMPOSITION/INFORMATION ON INGREDIENTS:

NAME	CAS No.:	CONTENT	SYMBOL:	RISK:
ACETONE	67-64-1	30-60 %	Xi ,F	R-11, 36, 66, 67
ISOBUTYL ACETATE	110-19-0	5-10 %	F	R-11, 66
XYLENE-ortho	95-47-6	1-5 %	Xn	R-10, 20/21, 38
PROPAN-2-OL	67-63-0	1-5 %	Xi ,F	R-11, 36, 67
DIBUTYL PHTHALATE	84-74-2	0-1 %	Xn	R-62, 63
BUTANE	106-97-8	5-10 %	Fx	R-12
ISOBUTANE	75-28-5	1-5 %	Fx	R-12
PROPANE	74-98-6	10-30 %	Fx	R-12
TOLUENE	108-88-3	10-30 %	Xn ,F	R-11, 20

3. HAZARDS IDENTIFICATION:

Extremely flammable. Harmful by inhalation. Irritating to eyes. Repeated exposure may cause skin dryness or cracking.

4. FIRST AID MEASURES:

GENERAL: Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

INHALATION:	Move the exposed person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering 100% oxygen. Keep the affected person warm and at rest. Get prompt medical attention.
INGESTION:	Do not induce vomiting. If vomiting occurs, the head should be kept low so that stomach vomit doesn't enter the lungs.
SKIN:	Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.
EYES:	Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

5. FIRE FIGHTING MEASURES:

EXTINGUISHING MEDIA:	Use: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.
SPECIAL FIRE FIGHTING PROCEDURES:	Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.
UNUSUAL FIRE & EXPLOSION HAZARDS:	Aerosol cans may explode in fires.

6. ACCIDENTAL RELEASE MEASURES:

SPILL CLEANUP METHODS:	Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Let evaporate. Keep out of confined spaces because of explosion risk. If leakage cannot be stopped, evacuate area.
-------------------------------	---

7. HANDLING AND STORAGE:

USAGE PRECAUTIONS:	Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.
STORAGE PRECAUTIONS:	Aerosol cans: Must not be exposed for direct sunlight or temperatures above 50°C.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION:

INGREDIENT NAME:	CAS No.:	STD	LT EXP 8 Hrs	ST EXP 15 Min
TOLUENE	108-88-3	OES.	50 ppm(Sk)	150 ppm(Sk)
ACETONE	67-64-1	OES.	750 ppm	1500 ppm
ISOBUTYL ACETATE	110-19-0	OES.	150 ppm	187 ppm
PROPAN-2-OL	67-63-0	OES.	400 ppm	500 ppm
DIBUTYL PHTHALATE	84-74-2	OES.	5 mg/m3	10 mg/m3
BUTANE	106-97-8	OES.	600 ppm	750 ppm
PROPANE	74-98-6		Asphyxiating	Asphyxiating

INGREDIENT COMMENTS: OES = Occupational Exposure Standard. MEL = Maximum Exposure Limit.

PROTECTIVE EQUIPMENT:



VENTILATION:	Provide adequate general and local exhaust ventilation.
RESPIRATORS:	No specific recommendation made, but respiratory protection must be used if the general level exceeds the Occupational Exposure Level (OEL).
PROTECTIVE GLOVES:	Use protective gloves.
EYE PROTECTION:	Use eye protection.
OTHER PROTECTION:	Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.
HYGIENIC WORK PRACTICES:	DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. No eating or drinking while working with this material.

9. PHYSICAL AND CHEMICAL PROPERTIES:

APPEARANCE:	Aerosol. Liquid.
COLOUR:	Varying.
ODOUR/TASTE:	Organic solvents.

10. STABILITY AND REACTIVITY:

STABILITY:	Normally stable.
CONDITIONS TO AVOID:	Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidising agents. Strong alkalis. Strong mineral acids.
HAZARDOUS DECOMP. PRODUCTS:	Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO ₂).

11. TOXICOLOGICAL INFORMATION:

HEALTH HAZARDS, GENERAL:	Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.
INHALATION:	Harmful by inhalation.
INGESTION:	May cause severe internal injury.
SKIN:	Prolonged or repeated contact leads to drying of skin. Product has a defatting effect on skin.
EYES:	Irritating to eyes.
HEALTH WARNINGS:	May cause irritation to the respiratory system. Solvent vapours are hazardous and may cause nausea, sickness and headaches. Prolonged inhalation of high concentrations may damage respiratory system. Product has a defatting effect on skin. May cause skin irritation/eczema. Irritating to eyes.
ROUTE OF ENTRY:	Inhalation. Skin and/or eye contact.

12. ECOLOGICAL INFORMATION:

ECOLOGICAL INFORMATION: No data is available on the product itself

13. DISPOSAL CONSIDERATIONS:

DISPOSAL METHODS: Empty containers must not be burned because of explosion hazard. Dispose of in accordance with Local Authority requirements.

14. TRANSPORT INFORMATION:

GENERAL: LIMITED QUANTITIES derogation applies to volumes under 1Lt

LABEL FOR CONVEYANCE:



ADR CLASS No.: 2.1
ADR CLASS: Division 2.1: Flammable gases.
ADR ITEM No.: 5F
ADR MARGINAL: 2201
ADR LABEL No.: 2.1
CEFIC TEC(R) No.: 20G26-2
PROPER SHIPPING NAME I: AEROSOLS
UN No. SEA: 1950
EmS No.: 2-13
MARINE POLLUTANT: N/A.
UN No., AIR: 1950

15. REGULATORY INFORMATION:

LABEL FOR SUPPLY:



RISK PHRASES:	R-12 Extremely flammable. R-20 Harmful by inhalation. R-36 Irritating to eyes. R-66 Repeated exposure may cause skin dryness or cracking.
SAFETY PHRASES:	S-2 Keep out of reach of children. S-16 Keep away from sources of ignition - No Smoking. S-26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S-51 Use only in well ventilated areas. S-23A Do not breathe gas/fumes/vapour/spray.
UK REGULATORY REFERENCES:	Petroleum (Consolidation) Act, as amended 1984 SI 1244. Highly Flammable Liquid Regulations 1972.
ENVIRONMENTAL LISTING:	Rivers (Prevention of Pollution) Act 1961. Control of Pollution (Special Waste Regulations) Act 1980.
EU DIRECTIVES:	System of specific information relating to Dangerous Preparations. 91\155.
APPROVED CODE OF PRACTICE:	Classification and Labelling of Substances and Preparations Dangerous for Supply.
GUIDANCE NOTES:	Occupational Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).

16. OTHER INFORMATION:

ISSUED BY:	Colin Sawmy
REV. No./REPL. SDS GENERATED:	1/
SDS No.:	10146
SAFETY DATA SHEET STATUS:	Approved.
DATE:	3/10/01
PRINTING DATE:	2002-02-21